

I-25-06-SS

Brand: Landscape Irrigation

Product Line: Rotors

Product Model: I-25

SKU: I2506SS

Description: I-25 Rotor, 6", adjustable from 50° to 360°, 1" inlet, stainless steel riser, check valve, five nozzles included



Dimensions

Height: 10.25"

Pop-up Height: 6"

Diameter: 1.75"



Operating Specifications

Arc: 50° to 360°

Operating Pressure: 40 to 100 PSI

Precipitation Rate: 0.4 in/hr

Radius: 37' to 71'

Flow: 3.8 to 31.5 GPM

Shipping Information

UPC-A: 0611698156179

Qty. / Bag: 12

Ocean Pallet: 1260

Land Pallet: 1080

Master Carton: 12

I-25 Nozzle Performance Data					
Nozzle	Pressure	Radius	Flow	Precip in/hr	
	PSI	ft	GPM		
4  Yellow	40	40	3.8	0.46	0.53
	50	41	4.3	0.49	0.57
	60	42	4.7	0.51	0.59
	70	43	5.1	0.53	0.61
7  Orange*	40	45	6.6	0.63	0.72
	50	47	7.0	0.61	0.70
	60	48	7.5	0.63	0.72
	70	49	7.9	0.63	0.73
8  Lt. Brown	40	47	7.7	0.67	0.77
	50	49	8.3	0.67	0.77
	60	50	9.2	0.71	0.82
	70	51	9.9	0.73	0.85
10  Lt. Green*	50	51	10.1	0.75	0.86
	60	52	11.1	0.79	0.91
	70	53	12.1	0.83	0.96
	80	54	12.9	0.85	0.98
13  Lt. Blue	50	53	11.2	0.77	0.89
	60	54	12.3	0.81	0.94
	70	55	13.3	0.85	0.98
	80	55	14.3	0.91	1.05
15  Grey*	50	56	13.4	0.82	0.95
	60	57	14.3	0.85	0.98
	70	57	15.2	0.90	1.04
	80	58	16.4	0.94	1.08
18  Red	50	58	14.5	0.83	0.96
	60	59	15.7	0.87	1.00
	70	62	16.9	0.85	0.98
	80	63	18.2	0.88	1.02
20  Dk. Brown*	60	62	17.8	0.89	1.03
	70	63	19.2	0.93	1.08
	80	64	20.5	0.96	1.11
	90	65	21.8	0.99	1.15
23  Dk. Green	60	64	21.9	1.03	1.19
	70	65	23.6	1.08	1.24
	80	66	25.6	1.13	1.31
	90	67	27.0	1.16	1.34
25  Dk. Blue*	60	66	23.5	1.04	1.20
	70	68	25.5	1.06	1.23
	80	69	28.0	1.13	1.31
	90	70	29.5	1.16	1.34
28  Black	70	68	26.9	1.12	1.29
	80	70	28.7	1.13	1.30
	90	71	30.6	1.17	1.35
	100	71	31.5	1.20	1.39
* 5 standard nozzles included with each sprinkler.					
Notes: All precipitation rates calculated for 180 degree operation. For the precipitation rate for a 360 degree sprinkler, divide by 2.					

I-25 High Speed Nozzle Performance Data					
Nozzle	Pressure	Radius	Flow		
	PSI	ft	GPM		
4  Yellow	40	37	3.8	0.53	
	50	38	4.3	0.57	
	60	38	4.7	0.63	
	70	39	5.2	0.66	
7  Orange*	40	40	6.1	0.73	
	50	41	6.9	0.79	
	60	42	7.5	0.82	
	70	44	8.1	0.81	
8  Lt. Brown	40	47	7.7	0.67	
	50	49	8.3	0.67	
	60	50	9.2	0.71	
	70	51	9.9	0.73	
10  Lt. Green*	50	46	10.1	0.92	
	60	48	11.1	0.93	
	70	49	12.1	0.97	
	80	50	12.9	0.99	
13  Lt. Blue	50	48	11.2	0.94	
	60	49	12.3	0.99	
	70	51	13.3	0.98	
	80	51	14.3	1.06	
15  Grey*	50	49	13.4	1.07	
	60	51	14.3	1.06	
	70	53	15.2	1.04	
	80	54	16.4	1.08	
18  Red	50	50	14.5	1.12	
	60	53	15.7	1.08	
	70	55	16.9	1.08	
	80	57	18.2	1.08	
20  Dk. Brown*	60	53	17.8	1.22	
	70	56	19.2	1.18	
	80	58	20.5	1.17	
	90	59	21.8	1.21	
23  Dk. Green	60	56	21.9	1.34	
	70	58	23.6	1.35	
	80	60	25.6	1.37	
	90	61	27.0	1.40	
25  Dk. Blue*	60	58	23.5	1.34	
	70	62	25.5	1.28	
	80	64	28.0	1.32	
	90	66	29.5	1.30	
28  Black	70	60	26.9	1.44	
	80	62	28.7	1.44	
	90	65	30.6	1.39	
	100	67	31.5	1.35	
* 5 standard nozzles included with each sprinkler.					
Notes: All precipitation rates calculated for 180 degree operation. For the precipitation rate for a 360 degree sprinkler, divide by 2.					

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/irrigation-product/i-25/i-25-06-ss>
020326