



PCB-25-R

Brand: Landscape Irrigation

Product Line: Nozzles

Product Model: Bubblers & Bubbler Nozzles

SKU: PCB25R

Description: Pressure-Compensating Bubbler, flood pattern, 0.25 GPM, ½" thread, reclaimed water ID

Shipping Information

UPC-A: 0611698145883

Qty. / Bag: 25/250

Ocean Pallet: 48000

Land Pallet: 40000

Master Carton: 250

Multi-Stream Bubbler Performance Data				
Arc		Model	Flow	Radius
			GPM	ft
		MSBN-25V *	0.25	1.5
		MSBN-50V *	0.50	2.5
		MSBN-25Q	0.25	1.0
		MSBN-50Q	0.50	1.5
		MSBN-50H	0.50	1.0
		MSBN-10H	1.00	1.5
		MSBN-10F	1.00	1.0
		MSBN-20F	2.00	1.5
Note: Typical spacing 2 to 4 ft. Flows shown for pressures between 15 and 70 PSI. *For a 6" pop-up, the radius is 2' at 0.25 GPM and 3' at 0.50 GPM				

PCN / PCB Performance Data			
	Model	Flow	Pattern
		GPM	Type
	25	0.25	Trickle
	50	0.50	Trickle
	10	1.00	Umbrella
	20	2.00	Umbrella
Note: Typical spacing 2 to 4 ft. Flows shown for pressures between 15 and 70 PSI.			

AFB Performance Data			
	Model	Flow	Pattern
		GPM	Type
	AFB	< 2.0	Trickle / Umbrella

5-CST-B Bubbler Nozzle Performance Data			
	Pressure	Radius	Flow
	PSI	ft	GPM
	20	5	0.30
	25	5	0.32
	30	5	0.38
	35	5	0.40
	40	5	0.42