

Pro High-Efficiency Nozzles

Adjustable arc spray nozzles with high uniformity and matched precipitation maximize water efficiency in spray sprinkler applications.

KEY BENEFITS

- High-efficiency performance from a high-uniformity spray pattern
- Matched precipitation of 1.6 in/hr from 8' to 17'
- Simple 0 to 360 arc adjustment using the easy-grip nozzle top
- Thick nozzle top offers long-lasting durability against equipment damage
- Fast installation with clear identification of spray pattern edges
- Full shutoff capability at 0 arc setting
- Color-coded with natural hues to blend seamlessly with the landscape and provide easy field identification
- Smooth spray pattern with well-defined edges for targeted landscape irrigation
- Recommended operating pressure: 30 psi
- Pair with Pro-Spray PRS30 Sprinkler Body for pressure regulation up to 30 psi
- Warranty period: 2 years



8A-HE OLIVE GREEN *

Radius: 8'

Adjustable from 0° to 360°

Trajectory 20°

Arc	Pressure	Radius	Flow	Precip in/hr	
	PSI	ft.	GPM	■	▲
90° 	20	7	0.23	1.81	2.09
	25	7	0.27	2.12	2.45
	30	8	0.28	1.68	1.95
	35	8	0.32	1.93	2.22
	40	9	0.35	1.66	1.92
180° 	20	7	0.44	1.71	1.97
	25	7	0.49	1.93	2.22
	30	8	0.55	1.65	1.90
	35	8	0.63	1.88	2.17
	40	9	0.68	1.62	1.87
270° 	20	7	0.65	1.71	1.97
	25	7	0.74	1.93	2.22
	30	8	0.82	1.65	1.90
	35	8	0.94	1.88	2.17
	40	9	1.02	1.62	1.87
360° 	20	7	0.87	1.71	1.97
	25	7	0.98	1.93	2.22
	30	8	1.10	1.65	1.90
	35	8	1.25	1.88	2.17
	40	9	1.26	1.62	1.87

10A-HE DARK BLUE •

Radius: 10'
Adjustable from 0° to 360°
Trajectory 25°

Arc	Pressure	Radius	Flow	Precip in/hr	
	PSI	ft.	GPM	■	▲
90° 	20	9	0.36	1.71	1.98
	25	9	0.41	1.95	2.25
	30	10	0.44	1.69	1.96
	35	10	0.48	1.85	2.13
	40	10	0.51	1.96	2.27
180° 	20	9	0.70	1.66	1.92
	25	9	0.78	1.85	2.13
	30	10	0.86	1.65	1.90
	35	10	0.93	1.79	2.07
	40	10	1.00	1.93	2.22
270° 	20	9	1.05	1.66	1.97
	25	9	1.17	1.85	2.22
	30	10	1.28	1.65	1.90
	35	10	1.40	1.79	2.07
	40	10	1.50	1.93	2.22
360° 	20	9	1.40	1.66	1.92
	25	9	1.55	1.85	2.13
	30	10	1.71	1.65	1.90
	35	10	1.86	1.79	2.07
	40	10	2.00	1.93	2.22

12A-HE BROWN •

Radius: 12'
Adjustable from 0° to 360°
Trajectory 25°

Arc	Pressure	Radius	Flow	Precip in/hr	
	PSI	ft.	GPM	■	▲
90° 	20	11	0.53	1.69	1.95
	25	11	0.59	1.88	2.17
	30	12	0.63	1.68	1.95
	35	12	0.70	1.87	2.16
	40	12	0.75	2.01	2.32
180° 	20	11	1.03	1.63	1.88
	25	11	1.12	1.78	2.06
	30	12	1.22	1.63	1.88
	35	12	1.33	1.78	2.05
	40	12	1.46	1.95	2.25
270° 	20	11	1.54	1.63	1.88
	25	11	1.68	1.78	2.06
	30	12	1.83	1.63	1.88
	35	12	2.00	1.78	2.05
	40	12	2.19	1.95	2.25
360° 	20	11	2.05	1.63	1.88
	25	11	2.24	1.78	2.06
	30	12	2.44	1.63	1.88
	35	12	2.66	1.78	2.05
	40	12	2.92	1.95	2.25

15A-HE BLACK •

Radius: 15'
Adjustable from 0° to 360°
Trajectory 25°

Arc	Pressure	Radius	Flow	Precip in/hr	
	PSI	ft.	GPM	■	▲
90° 	20	14	0.78	1.53	1.77
	25	14	0.88	1.73	2.00
	30	15	0.96	1.64	1.90
	35	15	1.07	1.83	2.11
	40	15	1.13	1.93	2.23
180° 	20	14	1.53	1.50	1.73
	25	14	1.69	1.66	1.91
	30	15	1.87	1.60	1.85
	35	15	2.05	1.75	2.03
	40	15	2.22	1.90	2.19
270° 	20	14	2.29	1.50	1.73
	25	14	2.53	1.66	1.91
	30	15	2.81	1.60	1.85
	35	15	3.08	1.75	2.03
	40	15	3.33	1.90	2.19
360° 	20	14	3.05	1.50	1.73
	25	14	3.37	1.66	1.91
	30	15	3.74	1.60	1.85
	35	15	4.10	1.75	2.03
	40	15	4.43	1.90	2.19

17A-HE GREY °

Radius: 17'
Adjustable from 0° to 360°
Trajectory 25°

Arc	Pressure	Radius	Flow	Precip in/hr	
	PSI	ft.	GPM	■	▲
90° 	20	16	0.95	1.43	1.66
	25	16	1.07	1.60	1.85
	30	17	1.24	1.65	1.91
	35	17	1.29	1.72	1.99
	40	17	1.39	1.85	2.13
180° 	20	16	1.77	1.33	1.53
	25	16	2.04	1.53	1.77
	30	17	2.36	1.57	1.82
	35	17	2.47	1.64	1.90
	40	17	2.65	1.77	2.04
270° 	20	16	2.65	1.33	1.53
	25	16	3.05	1.53	1.77
	30	17	3.54	1.57	1.82
	35	17	3.70	1.64	1.90
	40	17	3.98	1.77	2.04
360° 	20	16	3.53	1.33	1.53
	25	16	4.07	1.53	1.77
	30	17	4.72	1.57	1.82
	35	17	4.93	1.64	1.90
	40	17	5.30	1.77	1.53

Bold = Recommended pressure

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/irrigation-product/pro-high-efficiency-nozzles>
020326