

NODE

This battery-powered, waterproof controller offers automatic irrigation control for temporary irrigation and sites without electricity.

KEY BENEFITS

- Number of stations: 1, 2, 4, or 6
- Battery-operated controller for automatic irrigation without AC power
- Battery-life indicator for battery replacement
- Waterproof enclosure seal protects against water ingress
- 3 flexible programs with 4 start times each and up to 6-hour run times
- Suspend irrigation up to 99 days during the off-season
- Easy Retrieve™ Memory backs up the full irrigation schedule if ever changed
- Seasonal adjustment for quicker schedule adjustments without changing run times
- Solar panel provides maintenance-free operation
- Mounts to Hunter solenoids, pipes, flat surfaces, or inside the valve box



Operating Specifications

- One or two 9V alkaline batteries or 1800 mAh solar panel with charging cell
- Operates Hunter DC-latching solenoids (P/N 458200)
- 100' maximum wire runs, 18 AWG wire only
- Station output: 9-11 VDC
- P/MV output: 9-11 VDC (multi-station models)
- Sensor inputs: 2 (wired soil plus wired rain, freeze, or wind only)
- Approvals: IP68 (submersible), UL, cUL, FCC, CE, RCM, ISED
- Warranty period: 2 years

Maximum Wire Run

Wire Size Max Distance (ft)

18 AWG	100
--------	-----

Copyright © 2025 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/irrigation-product/controllers/node121625>