X2™ with WAND

This online-capable controller offers rapid schedule programming and advanced water-saving features.

KEY BENEFITS

- Number of stations: 4, 6, 8, or 14 (fixed models)
- Wi-Fi capable controller automatically managed by Hydrawise® software
- Backlit display provides optimal visibility in any light
- 3 flexible programs with 4 start times each and up to 6-hour run times
- QuickCheck™ provides simple diagnostics of faulty field wiring
- Hide Programs option shows 1 program and 1 start time for simplification
- Suspend irrigation up to 99 days during the offseason
- Short-circuit protection detects wiring faults and skips the station without system damage
- Easy Retrieve® memory backs up the full irrigation schedule
- Delay Between Stations for slow-closing valves or pump recharge
- Cycle and Soak prevents water waste and runoff in areas with elevation changes or tight soils
- Seasonal adjustment for quicker schedule adjustments without changing run times
- WAND WI-FI MODULE BENEFITS
- Simple Wi-Fi plug-in enables remote irrigation management with any X2 Controller
- · WAND Technology provides easy online irrigation management with controller status and faulty wiring alerts
- Standard programming allows for three independent programs featuring six start times each and 24-hour maximum run times
- Rapid Programming™ Technology lets you send preprogrammed schedules to any X2 Controller in seconds, so you get jobs done quicker
- Predictive Watering™ Technology provides precise weather adjustments for maximum water savings
- Compatibility with HomeSeer home automation technology enables simple, centralized voice control of the irrigation system
- Bluetooth Wi-Fi setup or WPS push-button connection makes it easy to connect to a wireless network

OPERATING SPECIFICATIONS

• Transformer input: 120 VAC

• Transformer output (24 VAC): 1 A

• Station output (24 VAC): 0.56 A

• P/MV output (24 VAC): 0.28 A

• Total maximum output: 0.84 A

• Sensor inputs: 1

- Supported security protocols: WPA/WPA2 Personal (only), TLS
- Approvals (controller): IP44, UL, cUL, FCC, CE, UKCA, RCM
- Approvals (module): Wi-Fi 2.4 gHz b/g/n, Bluetooth 5.0, UI, cUL, FCC, CE, RCM
- Warranty period: 2 years (controller and module)



 $https://api.hunterirrigation.com/irrigation-product/controllers/x2tm-wand \\121625$