

PGV-ASV

The Hunter PGV-ASV Anti-Siphon Valve is a backflow prevention device and irrigation control valve for sprinkler irrigation systems. Gain simple and trouble-free operation without the need for a separate backflow preventer. Ensure installation is in a region that allows for irrigation systems without backflow preventers. Always consult local construction codes.

PRINCIPAIS BENEFÍCIOS

- External/internal manual bleed allows for quick and easy activation at the valve
- Double-beaded diaphragm seal design ensures leak-free performance
- Captive bonnet screws eliminate the possibility of lost parts during disassembly
- Triple-tool bonnet screws are compatible with standard or Phillips screwdrivers as well as a nut driver
- Removable anti-siphon cap for simple servicing
- Encapsulated solenoid with captive plunger used on every Hunter valve provides hassle-free service
- Flow control maximizes efficiency and prolongs the life of the system



User-Installed Options

- Accu Sync® pressure regulation at the valve
- DC-latching solenoid for battery-powered controllers (P/N 458200)

Factory-Installed Options

- DC: DC-latching solenoid for battery-powered controllers

Operating Specifications

- Flow: 0.2 to 40 GPM
- Recommended pressure range: 20 to 150 PSI
- Temperature rating: 150°F
- Warranty period: 2 years

PGV-ASV PRESSURE LOSS IN PSI		
Flow	¾"	1"
GPM		
1	1	1
5	2	2
10	2	2
15	3	3
20	6	6
25		6
30		9
35		16
40		20

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/pt/node/287>
020226