

Emissores pontuais de gotejamento

A quantidade certa de água, direto na planta

PRINCIPAIS BENEFÍCIOS

- Compensação de pressão
- Diferenciados por cores de acordo com a vazão
- Três variações de entrada: espigão de 6 mm, rosca de 10-32 e FPT de 1/2"
- Bordas ranhuradas para fixação fácil
- Espigão autoperfurante
- Tampa difusora opcional
- Diafragma autolimpante
- Período de garantia: 2 anos

especificações de operação

- Faixa de pressão recomendada: 1,4 a 3,5 bar; 140 a 350 kPa
- Filtragem mínima: 150 mesh; 100 microns



Gráfico de modelos de emissores

		Modelo	Tipo de entrada	Vazão (l/h)
	Azul	HE-050-B	Barbela autoperfurante	2,0
	Preto	HE-10-B	Barbela autoperfurante	4,0
	Vermelho	HE-20-B	Barbela autoperfurante	8,0
	Bege	HE-40-B	Barbela autoperfurante	15,0
	Laranja	HE-60-B	Barbela autoperfurante	23,0
	Azul	HE-050-T	Rosca de $\frac{10}{32}$	2,0

	Preto	HE-10-T	Rosca de $10/32$	4,0
	Vermelho	HE-20-T	Rosca de $10/32$	8,0
	Bege	HE-40-T	Rosca de $10/32$	15,0
	Laranja	HE-60-T	Rosca de $10/32$	23,0
	Azul	HEB-05	Rosca fêmea de $1/2$ "	2,0
	Azul	HEB-05-CV	Rosca fêmea de $1/2$ "	2,0

	Preto	HEB-10	Rosca fêmea de ½"	4,0
	Preto	HEB-10-CV	Rosca fêmea de ½"	4,0
	Vermelho	HEB-20	Rosca fêmea de ½"	8,0
	Vermelho	HEB-20-CV	Rosca fêmea de ½"	8,0
	Bege	HEB-40	Rosca fêmea de ½"	15,0
	Bege	HEB-40-CV	Rosca fêmea de ½"	15,0

	Laranja	HEB-60	Rosca fêmea de ½"	23,0
	Laranja	HEB-60-CV	Rosca fêmea de ½"	23,0

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/pt/irrigation-product/micro-irrigation/emissores-pontuais-de-gotejamento>
020326