

HDL-06-12-250-R



Marca: Irrigação paisagística

Linha de produtos: Microirrigação

Modelo de produto: HDL

SKU: HDL0612250R

Descrição: Tubo gotejador Hunter, compensação de pressão, 2,1 l/h, espaçamento de 30 cm, 75 m, para água residual

Shipping Information

UPC-A: 0611698514894

Quantidade/saco: 1

Palete oceânico: 44

Palete terrestre: 36

Caixa principal: 1

Additional Information

Taxa de vazão: 0.6 GPH

Comprimento da bobina: 250'

Espaçamento entre emissores: 12"

Taxa de vazão: 0.6 GPH

Irrigação em linha: Drip irrigation

Irrigação on-line: Tubulação

HDL 17 MM Pressure-Compensating and Reclaimed - Minimum Operating Pressure of 0.7 bar

HDL-PC and HDL-R - 2.5 L/hr

Pressure (bar)	Emitter Spacing (cm)		
	30	45	60
1.0	82	103	130
2.0	103	147	206
3.0	129	210	280
4.0	167	295	399

HDL 17 MM Check Valve - Minimum Operating Pressure of 1 bar

HDL-CV - 2.5 L/hr

Pressure (bar)	Emitter Spacing (cm)		
	30	45	60
1.0	62	88	112
2.0	106	163	207
3.0	142	200	250
4.0	184	280	389

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/pt/irrigation-product/hdl/hdl-06-12-250-r>
020326