



- 01 **Flexible design:** Modular station expansion allows conventional, two-wire, or hybrid control for up to 32 stations
- 02 **Remote operation:** Manage unlimited Pro-C Controllers from anywhere with the optional PC-WIFI™ Module
- 03 **Smarter irrigation:** Increase water savings with two sensor inputs that support Hunter Solar Sync® and Klik Sensors

PRO-C® CONTROLLER

The Professional's Choice for Residential and Light Commercial Systems

The next generation of Pro-C Controllers is here! The **P2C Series** builds on the trusted Pro-C line with all the features you love — like flexible station counts and intuitive programming — plus exciting new updates: a modern user interface, large backlit display, enhanced sensor capabilities, and optional Wi-Fi connectivity.

For decades, professionals have relied on the Pro-C for affordable, dependable irrigation control in a compact design. The P2C Series makes system expansion effortless with options for conventional wiring, EZ Decoder control, or hybrid two-wire setups, offering unmatched flexibility.

Save time and simplify management with the optional PC-WIFI Module, which lets you control unlimited Pro-C Controllers remotely via Centralus™ Software — for free.

Maximize water efficiency by pairing the Pro-C with a Solar Sync Sensor to achieve EPA WaterSense® approval and optimal water savings via automatic weather-based adjustments.

Learn more. Visit hunterirrigation.com or contact your local Sales Manager.



PRO-C FEATURES & SPECIFICATIONS

Key Benefits

- Number of stations:
 - Conventional wiring from 4 to 23 stations
 - Hybrid EZ Decoder option for up to 32 total stations (28 stations maximum if two-wire only)
- Optional PC-WIFI Module offers convenient online irrigation management
- 3 automatic irrigation programs with 4 start times per program and 6-hour run times per station
- 2 sensor inputs available for use with Solar Sync or any Klik Sensor
- 1 P/MV output for pump start relay and master valve activation
- High-visibility, backlit display for simple programming in any light
- Optional Seconds Mode allows for station run times with seconds resolution from 1 second to 5 minutes
- Easy Retrieve® Memory allows for manual backup and retrieval of preferred settings and programming
- QuickCheck™ Technology provides simple diagnostics of faulty field wiring
- Backward compatible with previous modular PC-400 models dated 2014 to 2023

Operating Specifications

- Transformer input: 120 VAC
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- Approvals: IP44 (outdoor), UL, cUL, FCC, CE, UKCA, RCM, ISED
- PC-WIFI Module
 - 2.4 GHz (only) Wi-Fi router compatible, 802.11 b/g/n
 - Supported security protocols: WPA/WPA2 Personal (only), TLS
- Warranty period: 2 years



EPA WaterSense

Add the WaterSense® labeled Solar Sync Sensor to improve the water efficiency of this controller.

Model

Plastic Outdoor

Height: 9"
Width: 10"
Depth: 4½"



PCM-300



PCM-900



PCM-1600



PC-DM



PC-WIFI

PRO-C	
Model	Description
P2C-400	4-station base, plastic wall mount cabinet with cable and plug
PCM-300	3-station plug-in module
PCM-900	9-station plug-in module
PCM-1600	16-station plug-in module
PC-DM	EZ Decoder output module
PC-WIFI	Plug-in Wi-Fi module for Pro-C Controllers

Website hunterirrigation.com | **Customer Support** 1-800-383-4747

Helping our customers succeed is what drives us. While our passion for innovation and engineering is built into everything we do, it is our commitment to exceptional support that we hope will keep you in the Hunter family of customers for years to come.

Denise Mullikin, President,
Landscape Irrigation and Outdoor Lighting