

ICC2

This flexible control system can run any combination of conventional, EZ Decoder two-wire, or Wireless Valve Link outputs with built-in flow monitoring and convenient, online control with Centralus™ Software.

KEY BENEFITS

- Number of stations:
 - Conventional: 8 to 38 (plastic), 8 to 54 (metal and pedestals)
 - With two-wire EZDS: up to 54 (all enclosure options)
 - With Wireless Valve Link (WVL): up to 54 (all enclosure options)
- 4 automatic irrigation programs with 8 start times per program and 12-hour run times per station
- Any 2 programs can operate simultaneously, providing more efficient watering
- 2 sensor inputs for dedicated flow sensor and weather sensor connections
- Built-in flow monitoring for smart water savings
- 1 P/MV output for pump start relay and master valve activation
- Upgradable to Centralus Software for web-based central control options

OPERATING SPECIFICATIONS

- Transformer input: 120/230 VAC
- Transformer output (24 VAC): 1.4 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.56 A
- Approvals: Wall Mounts IP55 (outdoor), Plastic Pedestal IP24, UL, cUL, FCC, CE, UKCA, RCM, ISED
- Warranty period: 5 years

USER-INSTALLED OPTIONS

- WIFIKIT, LANKIT, or CELLKIT communications for cloud-based Centralus control
- Compatible with Hunter Flow-Sync® Sensor for standalone flow monitoring connections
- SCADA/automation compatible with BACnet, Modbus, and other protocols via Hunter 360 Software
- Compatible with ROAM and ROAM XL Remotes

View Centralus Software today
at centralus.hunterindustries.com.



Plastic

Height: 12"
Width: 13¾"
Depth: 5"

Metal

(gray or stainless steel)
Height: 16"
Width: 13"
Depth: 5"



Metal Pedestal

(gray or stainless steel)
Height: 36"
Width: 11½"
Depth: 5"



Plastic Pedestal

Height: 39"
Width: 24"
Depth: 17"

ICC2 FLOW CAPABLE CONTROLLERS

Model	Description
I2CF-800-PL	8-station base model, plastic outdoor wall mount
I2CF-800-M	8-station base model, gray metal outdoor wall mount
I2CF-800-SS	8-station base model, stainless steel wall mount
I2CF-800-PP	8-station base model, plastic pedestal
ICCF-FPUP2	ICC2 Retrofit Kit for original ICC Controllers
ICC-PED	Gray pedestal for metal controller mount
ICC-PED-SS	Stainless steel pedestal for stainless steel controller mount
ICC-PWB	Optional pedestal wiring board for metal pedestals

ICC2 SERIES STATION EXPANSION

Model	Description
ICM-400	4-station plug-in module with enhanced surge suppression
ICM-800	8-station plug-in module with enhanced surge suppression
ICM-2200	22-station expansion module (one per controller)
EZDS	See hunter.info/EZDS
WVL	See hunter.info/WVL


Compatible with:



Solar Sync
Sensor



Wireless Valve
Link



EZ Decoder
System



EPA WaterSense® Approved

Recognized as a responsible water-saving tool when used with a Solar Sync Sensor