



## MP-3000-HT-210

**Marka:** Peyzaj Sulama

**Ürün Serisi:** MP Rotator Nozullar

**Ürün Modelleri:** Standart MP Rotator Nozul

**Stok Kodu:** MP3000HT210

**Açıklama:** MP Rotator Nozul, 10 mm/saat yağış hızı, 6,7 m ila 9 m yarıçap, 210° ila 270° ayarlanabilir yay, erkek dişli, sarı

### Operating Specifications

**Arc:** 210° to 270°

**Operating Pressure:** 2,8 bar; 280 kPa

**Precipitation Rate:** 10 mm/sa

**Radius:** 8,2 - 9,1 m

**Flow:** 0,42 - 0,57 m3/sa; 6,97 - 9,44 l/dk

### Shipping Information

**UPC-A:** 0611698153215

**Adet / Çanta:** 10/200

**Okyanus Paleti:** 38400

**Kara Paleti:** 32000

**Ana Karton:** 200

### Additional Information

**Ark Seçeneği:** 210° - 270°

**Yağmurlama Oranı:** Approx 0.4 in/hr

**Atış mesafesi:** 22' - 30'



# MP ROTATOR PERFORMANS VERİLERİ

## MP1000

**Atış Mesafesi:** 2,5 ile 4,5 m  
Ayarlanabilir Açı ve Tam Daire

**Bordo:** 90° - 210°

**Açık Mavi:** 210° - 270°

**Koyu Yeşil:** 360°

| Açı                                                                                        | Basınç |     |  |  | Atış Mesafesi | Debi  |      | Yağmurlama mm/sa |    |
|--------------------------------------------------------------------------------------------|--------|-----|--|--|---------------|-------|------|------------------|----|
|                                                                                            | bar    | kPa |  |  | m             | m³/sa | l/dk | ■                | ▲  |
| 90°<br>   | 1,7    | 170 |  |  | -             | -     | -    | -                | -  |
|                                                                                            | 2,0    | 200 |  |  | 3,7           | 0,04  | 0,64 | 11               | 13 |
|                                                                                            | 2,5    | 250 |  |  | 4,0           | 0,04  | 0,72 | 11               | 13 |
|                                                                                            | 2,8    | 280 |  |  | 4,1           | 0,05  | 0,80 | 11               | 13 |
|                                                                                            | 3,0    | 300 |  |  | 4,3           | 0,05  | 0,87 | 11               | 13 |
|                                                                                            | 3,5    | 350 |  |  | 4,5           | 0,06  | 0,95 | 11               | 13 |
|                                                                                            | 3,8    | 380 |  |  | 4,5           | 0,06  | 1,02 | 12               | 14 |
| 180°<br>  | 1,7    | 170 |  |  | -             | -     | -    | -                | -  |
|                                                                                            | 2,0    | 200 |  |  | 3,7           | 0,08  | 1,29 | 11               | 13 |
|                                                                                            | 2,5    | 250 |  |  | 4,0           | 0,09  | 1,44 | 11               | 13 |
|                                                                                            | 2,8    | 280 |  |  | 4,1           | 0,10  | 1,59 | 11               | 13 |
|                                                                                            | 3,0    | 300 |  |  | 4,3           | 0,10  | 1,67 | 11               | 13 |
|                                                                                            | 3,5    | 350 |  |  | 4,5           | 0,12  | 1,90 | 11               | 13 |
|                                                                                            | 3,8    | 380 |  |  | 4,5           | 0,12  | 1,93 | 12               | 13 |
| 210°<br> | 1,7    | 170 |  |  | -             | -     | -    | -                | -  |
|                                                                                            | 2,0    | 200 |  |  | 3,7           | 0,09  | 1,52 | 12               | 13 |
|                                                                                            | 2,5    | 250 |  |  | 4,0           | 0,10  | 1,71 | 11               | 13 |
|                                                                                            | 2,8    | 280 |  |  | 4,1           | 0,11  | 1,86 | 11               | 13 |
|                                                                                            | 3,0    | 300 |  |  | 4,3           | 0,12  | 1,93 | 11               | 13 |
|                                                                                            | 3,5    | 350 |  |  | 4,5           | 0,13  | 2,16 | 11               | 13 |
|                                                                                            | 3,8    | 380 |  |  | 4,5           | 0,14  | 2,24 | 11               | 13 |
| 270°<br> | 1,7    | 170 |  |  | -             | -     | -    | -                | -  |
|                                                                                            | 2,0    | 200 |  |  | 3,7           | 0,11  | 1,82 | 11               | 12 |
|                                                                                            | 2,5    | 250 |  |  | 4,0           | 0,12  | 2,01 | 10               | 12 |
|                                                                                            | 2,8    | 280 |  |  | 4,1           | 0,14  | 2,39 | 11               | 13 |
|                                                                                            | 3,0    | 300 |  |  | 4,3           | 0,15  | 2,54 | 11               | 13 |
|                                                                                            | 3,5    | 350 |  |  | 4,5           | 0,17  | 2,73 | 11               | 13 |
|                                                                                            | 3,8    | 380 |  |  | 4,5           | 0,17  | 2,84 | 11               | 13 |
| 360°<br> | 1,7    | 170 |  |  | -             | -     | -    | -                | -  |
|                                                                                            | 2,0    | 200 |  |  | 3,7           | 0,16  | 2,62 | 12               | 13 |
|                                                                                            | 2,5    | 250 |  |  | 4,0           | 0,18  | 2,92 | 11               | 13 |
|                                                                                            | 2,8    | 280 |  |  | 4,1           | 0,19  | 3,18 | 11               | 13 |
|                                                                                            | 3,0    | 300 |  |  | 4,3           | 0,20  | 3,34 | 11               | 13 |
|                                                                                            | 3,5    | 350 |  |  | 4,5           | 0,23  | 3,71 | 11               | 13 |
|                                                                                            | 3,8    | 380 |  |  | 4,5           | 0,23  | 3,83 | 11               | 13 |

## MP2000

**Atış Mesafesi:** 4,0 ile 6,4 m  
Ayarlanabilir Açı ve Tam Daire

**Siyah:** 90° - 210°

**Yeşil:** 210° - 270°

**Kırmızı:** 360°

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/tr/irrigation-product/standart-mp-rotator-nozul/mp-3000-ht-210020326>