



eco-04-20-90

Marka: Peyzaj Sulama

Ürün Serisi: Pop Up Gövdeler

Ürün Modelleri: Eco-Rotator

Stok Kodu: ECO042090

Açıklama: Eco-Rotator Sprinkler, MP2000-90 Nozüllü 10 cm açılır pencere, 4 m ila 6,4 m yarıçap, 90 ° ila 210 °, geniş giriş filtresi ekranı ve ½" giriş

Operating Specifications

Arc: 90° to 210°

Operating Pressure: 2,8 bar; 280 kPa

Precipitation Rate: 10 mm/sa

Radius: 5,2 - 6,4 m

Flow: 0,09 - 0,11 m3/sa; 1,44 - 1,82 l/dk

Shipping Information

UPC-A: 0611698156995

Okyanus Paleti: 9000

Kara Paleti: 7200

Ana Karton: 50

Eco-Rotator Performans Verileri

MP1000

Atış Mesafesi: 2,5 - 4,6 m
Ayarlanabilir Açı ve Tam Daire
Bordo: 90° - 210°
Koyu Yeşil: 360°

Açı	Basınç				Atış Mesafesi	Debi		Yağmurlama mm/sa	
	bar	kPa			m	m³/sa	l/dk	■	▲
90° 	1,7	170			...	...	...	...	...
	2,0	200			3,7	0,04	0,61	11	12
	2,5	250			4,0	0,04	0,68	10	12
	2,8	280			4,1	0,04	0,70	10	11
	3,0	300			4,3	0,04	0,73	10	11
	3,5	350			4,4	0,05	0,78	10	11
	3,8	380			4,6	0,05	0,81	9	11
180° 	1,7	170			...	...	...	...	...
	2,0	200			3,7	0,07	1,20	11	12
	2,5	250			4,0	0,08	1,35	10	12
	2,8	280			4,1	0,08	1,40	10	11
	3,0	300			4,3	0,09	1,46	10	11
	3,5	350			4,4	0,09	1,56	10	11
	3,8	380			4,6	0,10	1,62	9	11
210° 	1,7	170			...	...	...	...	...
	2,0	200			3,7	0,09	1,41	11	13
	2,5	250			4,0	0,10	1,58	10	12
	2,8	280			4,1	0,10	1,63	10	11
	3,0	300			4,3	0,10	1,71	10	11
	3,5	350			4,4	0,11	1,82	10	11
	3,8	380			4,6	0,11	1,89	9	11
360° 	1,7	170			...	...	...	...	...
	2,0	200			3,5	0,14	2,40	12	14
	2,5	250			4,0	0,16	2,69	10	12
	2,8	280			4,1	0,17	2,81	10	12
	3,0	300			4,3	0,18	2,94	10	11
	3,5	350			4,4	0,19	3,17	10	11
	3,8	380			4,5	0,20	3,25	10	11

MP2000

Atış Mesafesi: 4 - 6,4 m
Ayarlanabilir Açı ve Tam Daire
Siyah: 90° - 210°
Kırmızı: 360°

Açı	Basınç				Atış Mesafesi	Debi		Yağmurlama mm/sa	
	bar	kPa			m	m³/sa	l/dk	■	▲

90°	1,7	170			5,2	0,07	1,18	11	12
	2,0	200			5,5	0,07	1,23	10	11
	2,5	250			5,8	0,09	1,43	10	12
	2,8	280			6,1	0,09	1,52	10	11
	3,0	300			6,4	0,09	1,57	9	11
	3,5	350			6,7	0,10	1,68	9	10
	3,8	380			6,7	0,11	1,77	9	11
180°	1,7	170			4,9	0,13	2,22	11	12
	2,0	200			5,2	0,14	2,35	11	12
	2,5	250			5,5	0,16	2,67	11	12
	2,8	280			5,8	0,17	2,80	10	12
	3,0	300			6,1	0,17	2,90	10	11
	3,5	350			6,4	0,19	3,15	9	10
	3,8	380			6,4	0,19	3,22	9	11
210°	1,7	170			4,9	0,16	2,58	11	12
	2,0	200			5,2	0,17	2,75	11	13
	2,5	250			5,5	0,19	3,08	10	12
	2,8	280			5,8	0,20	3,25	10	12
	3,0	300			6,1	0,21	3,42	10	11
	3,5	350			6,4	0,22	3,70	9	10
	3,8	380			6,4	0,23	3,80	10	11
360°	1,7	170			4,9	0,27	4,42	11	12
	2,0	200			5,2	0,28	4,72	11	13
	2,5	250			5,5	0,32	5,28	10	12
	2,8	280			5,8	0,33	5,55	10	12
	3,0	300			6,1	0,35	5,80	10	11
	3,5	350			6,4	0,37	6,25	9	10
	3,8	380			6,4	0,38	6,40	9	10

MP3000

Atış Mesafesi: 6,7 - 9,1 m
Ayarlanabilir Açı ve Tam Daire
Mavi: 90° - 210°
Gri: 360°

Açı	Basınç				Atış Mesafesi	Debi		Yağmurlama mm/sa	
	bar	kPa			m	m³/sa	l/dk		
90°	1,7	170			7,6	0,16	2,63	11	13
	2,0	200			8,2	0,17	2,77	10	11
	2,5	250			8,5	0,19	3,08	10	12
	2,8	280			9,1	0,20	3,25	9	11
	3,0	300			9,1	0,20	3,38	10	11
	3,5	350			9,1	0,22	3,67	11	12
	3,8	380			9,1	0,23	3,80	11	13
180°	1,7	170			7,6	0,32	5,48	11	13
	2,0	200			8,2	0,35	5,88	10	12
	2,5	250			8,5	0,40	6,55	11	12
	2,8	280			9,1	0,41	6,88	10	11
	3,0	300			9,1	0,43	7,18	10	12
	3,5	350			9,1	0,47	7,77	11	13
	3,8	380			9,1	0,45	8,02	12	13
210°	1,7	170			7,6	0,38	6,40	11	13
	2,0	200			8,2	0,41	6,85	10	12
	2,5	250			8,5	0,46	7,65	11	12
	2,8	280			9,1	0,48	8,02	10	11
	3,0	300			9,1	0,50	8,37	10	12
	3,5	350			9,1	0,54	9,03	11	13

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/tr/irrigation-product/eco-rotator/eco-04-20-90020326>