

I-Core™ için DUAL®

DUAL Dekoderlerin üretimi durduruldu.

ÖNEMLİ AVANTAJLARI

- 3 separate two-wire paths provide flexibility in system design and installation
- 1- and 2-station decoders available for use with a variety of valve manifolds
- Field-programmable decoders do not require serial numbers
- Decoders can be programmed before installation at the DUAL48M interface
- Wireless programming with ICD-HP allows for decoder programming or re-programming after installation to the two-wire path
- DUAL-S external surge protection module provides additional protection
- DUAL48M output module displays decoder programming, operation, and diagnostic information for assistance with maintenance and troubleshooting
- DUAL48M may be installed with conventional modules for hybrid operations
- Solenoid finder feature aids in locating decoders and valves in the field



Dual Model Specifications

- Maximum recommended distance, decoder to solenoid: 30 m
- Maximum distance to decoder:
 - 2 mm2 wire path: 1.5 km
 - 3.3 mm2 wire path: 2.3 km
- Approvals: UL, cUL, FCC, CE, RCM
- Decoder rating: IP68 submersible
- Warranty period: 2 years

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/tr/irrigation-product/kontrol-uniteleri/i-coretm-icin-dualr>
020326