

ACC

ACC DENETLEYİCİSİNİN YERİNİ ACC2 DENETLEYİCİSİ
ALMIŞTIR

ÖNEMLİ AVANTAJLARI

- İstasyon sayısı:
- Geleneksel: 12 - 42
- Dekoder: 1 - 99
- 6 otomatik program (her birinde 10 başlangıç zamanı)
- Büyük sistemleri birleştirmek için SSG'ler (Eş Zamanlı İstasyon Grupları)
- Akıllı su tasarrufu için dahili Solar Sync™ mantığı
- Gerçek zamanlı akış izleme, isteğe bağlı akış sensörü ile sızıntıları tespit ve teşhis eder
- Sade dilde ayrıntılı alarm günlükleri
- Sensör kapatıldıktan sonra Programlanabilir Yağmur Gecikmesi
- Easy Retrieve™ programlama yedekleme ve geri yükleme
- Yanlışlıkla sulamayı engellemek için Sulamasız Aralıklar
- Döngü ve Islatma, İstasyonlar Arası Gecikme



Operating Specifications

- Transformer input: 120/230 VAC
- Maximum AC current draw: 120 VAC, 2A/230 VAC, 1 A
- Transformer output: 24 VAC, 4 A
- Station outputs: 0.56 A
- 2 P/MV outputs (24 VAC): 0.325 A each
- Simultaneous program operation: Up to 6 automatic programs
- Sensor inputs: 4 Clik, 1 Solar Sync, and 1 Flow sensor
- Approvals: Wall Mounts IP44, Plastic Pedestal IP34, NEMA 3R, UL, cUL, FCC, CE, RCM
- Garanti süresi: 5 yıl

User-Installed Options

- Solar Sync smart weather sensor
- Flow sensor including Flow-Sync, WFS, and other approved equals
- ROAM/ROAM XL license-free remote control (pre-wired controller connection)
- Communication modules for IMMS™ central software

Additional Specifications by Model

Operating Specifications

- Transformer input: 120/230 VAC
- Maximum AC current draw: 120 VAC, 2A/230 VAC, 1 A
- Transformer output: 24 VAC, 4 A
- Station outputs: 0.56 A
- 2 P/MV outputs (24 VAC): 0.325 A each

- Simultaneous program operation: Up to 6 automatic programs
- Sensor inputs: 4 Clik, 1 Solar Sync, and 1 Flow sensor
- Approvals: Wall Mounts IP44, Plastic Pedestal IP34, NEMA 3R, UL, cUL, FCC, CE, RCM
- Garanti süresi: 5 yıl

User-Installed Options

- Solar Sync smart weather sensor
- Flow sensor including Flow-Sync, WFS, and other approved equals
- ROAM/ROAM XL license-free remote control (pre-wired controller connection)
- Communication modules for IMMS™ central software

Additional Specifications

ACC Conventional Wiring

- Number of stations:
 - 12 to 42
- Modular expansion in 6-station increments(A2M-600)
- Extreme service lightning protection, standard on all output modules

ACC-99D Two-Wire Decoder

- Number of stations:
 - 99 decoder stations
- Operates Hunter's premium ICD decoders over ID wire:
 - Up to 3 km (2 mm² wire)
 - Up to 4.5 km (3 mm² wire)
- Up to 6 two-wire paths for maximum flexibility
- 1-,2-,4-, and 6-station decoders plus ICD-SEN sensor input decoders

Copyright © 2026 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://api.hunterirrigation.com/tr/irrigation-product/artik-uretilmeyeyen-modeller/acc020326>